
HP Colorfast Adhesive Vinyl, 2 Pack





The HP Designjet printing system—the complete solution

HP Designjet printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



With Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, or Original HP 70 Photo Inks on the HP Designjet Z3200 Photo Printer series. Display permanence rating for interior displays/ away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see globalBMG.com/hp/t/ printpermanence.

Produce stunning up-close image quality

See premium image quality on this premium vinyl

Gain all the benefits a premium vinyl has to offer. With a permanent, pressure-sensitive adhesive, this vinyl resists peeling.

Look to the vinyl that can make your job easier

Gain efficiency. ICC profiles help you get the color you need quickly. Instant dry time helps keep your workflow moving. This versatile material is compatible with both HP dye-and pigment-based inks.

Produce images with broad appeal

Print sharp, lifelike images ideal for up-close viewing. With a broad color gamut, this presentation-quality vinyl produces long-lasting, sharp image quality and vibrant color for a wide range of POP, retail, and event displays.

g up close
r
sive
ay permanence
ginal HP dye- and

Technical specifications



HP Colorfast Adhesive Vinyl, 2 Pack

For the latest ICC/media profiles and a variety of resources to help you get the most out of your printer and HP large format printing materials, please visit **globalBMG.com/hp/**.

Weight (without liner)	100 a/m² por ICO	E26 Toct N	Anthod			
	190 g/m² per ISO 536 Test Method					
Weight (with liner)	345 g/m² per ISO 536 Test Method					
Thickness (without liner)	160 microns/6.3 mil per ISO 534 Test Method					
Thickness (with liner)	325 microns/12.8 mil per ISO 534 Test Method					
Opacity (with liner)	Greater than 95% per TAPPI T-425 Test Method, greater than 96% per ISO 2471 Test Method					
Brightness (with liner)	Greater than 90% per TAPPI T-452 Test Method, greater than 92% per ISO 2470 Test Method					
Whiteness (with liner)	112 per ISO 11476 Test Method, 130 per ISO 11475 Test Method					
Finish	Matte					
Operating temperature	15 to 35° C / 59 to 95° F					
Operating humidity	20 to 80% RH					
Display permanence	75+ years, unlaminated with Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, or Original HP 70 Photo					
(Indoor home or office)	Inks on the HP Designjet Z3200 Photo Printer series ³					
Water resistance	Moderately water resistant with Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, or Original HP 70					
	Photo Inks on the HP Designjet Z3200 Photo Printer series⁴					
Dry time	Less than 2 minutes (at 23° C, 50% RH)					
Lamination	Yes					
Shelf life	2 years, unopened in original packaging					
Storage temperature	15 to 35° C / 59 to 95° F					
Storage humidity	15 to 30% RH					
Country of origin	Product of China					
Ordering information	Product numbers	Quantity	Roll sizes	UPC codes	Region	
	COF08A	2 Pack	914 mm x 12,2 m (36 in x 40 ft)	848412012859	Worldwide	
	COF09A	2 Pack	1372 mm x 12,2 m (54 in x 40 ft)	848412012866	North America, Europe	
			, (,		,	

For detailed information on the HP large format print media portfolio and to order, visit globalBMG.com/hp.

© 2014 Hewlett-Packard Development Company. © 2014 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of Hewlett-Packard Company and is used by Brand Management Group on license from Hewlett-Packard Company.



³ Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see globalBMG.com/hp/t/printpermanence.

Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see: <u>globalBMG.com/hp/t/</u> <u>printpermanence</u>.