



KODAK

Backlit film, Glossy / 8 mil / Solvent

Vibrant light box applications

Vibrant color

Compatible with solvent and low solvent printers, KODAK Backlit Film, Glossy / 8 mil / Solvent is a gloss-coated polyester backlit film used to produce vibrant light box applications.

Durable and easy to handle

The heavyweight front-print backlit film is a durable polyester with exceptional color saturation that dries quickly to ensure easy handling and finishing in production.

FEATURES:

- Heavy and rigid for smooth production
- One-step gloss-coated polyester backlit film
- Compatible with solvent and low-solvent printers

APPLICATIONS:

- Backlit airport signage
- Backlit mall and shopping center signage
- Non-backlit display applications

US Size	Euro Size	Quantity	SKU
24" x 100'	61 cm x 30,5 m	1 Roll	KUBLFG24
36" x 100'	91,4 m x 30,5 m	1 Roll	KUBLFG36
42" x 100'	106,7 cm x 30,5 m	1 Roll	KUBLFG42
50" x 100'	127 cm x 30,5 m	1 Roll	KUBLFG50
60" x 100'	152,4 cm x 30,5 m	1 Roll	KUBLFG60





Backlit Film, Glossy / 8 mil / Solvent

Properties	Specifications
Material	Polyester film
Gauge	8 mil
Base Weight	280g
Gloss Level	>=35
Whiteness	>92 CEI
Printer/Ink Compatibility	Compatible with solvent and eco-solvent inks.
Software Settings	Please refer to www.brandmanagementgroup.com for ICC profiles for some printers.
Finishing/Post Processing	It is always recommended that a protective laminate be applied after printing. Hand applying a laminate is not recommended. Pressure-sensitive can be used. Before applying the laminate, allow the image to dry for 24 hours.
Optimal Service Environment	72° F (21° C), 50% R.H. For end use: 0-300° F.
Handling Recommendations	It is suggested that you use the take-up reel with this product as the product could have a slight static charge that can cause the product to stick to the post heaters. It is also recommended that media clips are used to keep the media from bunching up if static is present. Avoid touching the coated surface and use cotton gloves when handling inkjet coated materials. Rolls of Kodak inkjet media come with the coated side facing out.
Ideal Storage Conditions	70° F (21° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the BMG ship date when stored in proper conditions.



KODAK Backlit Film, Glossy / 8 mil / Solvent

Product Performance & Suitability: All of the descriptive information and recommendations for the use of Kodak products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by BMG. All Purchasers of Kodak products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor the manufacturer shall be liable either in the tort in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect in agreement signed by officers of seller and manufacturer.

Eastman Kodak Company 343 State Street Rochester, NY 14650 USA +1-866-563-2533 in North America. Produced using Kodak Technology.
©Kodak, 2017. Kodak, Flexcel, Squarespot, Staccato and the Kodak Logo are trademarks of Kodak.
Subject to technical change without notice. U.FLX.865.0916.en.13

KODAKWFMedia.com

