



KODAK

Water-Resistant Poly Poster Matte / 8 mil

Long lasting, color-saturated displays

Economical and durable

KODAK Water-Resistant Poly Poster Matte produces deeply saturated, long-lasting prints. This versatile print material offers durability with water- and tear-resistance at a very economical price.

Produces beautiful displays

KODAK Water-Resistant Poly Poster Matte is great for indoor and outdoor signage, tradeshow displays, theater backdrops, shop-front displays and floor graphics (with acceptable laminate).

FEATURES:

- Compatible with dye and pigmented ink
- Water- and tear-resistant
- Economical alternative to scrim vinyl

APPLICATIONS:

- Short-term outdoor banners
- Signs and displays
- Banner stands

US Size	Euro Size	Quantity	SKU
36" x 100'	91,4 cm x 30,5 m	1 Roll	220061-00
42" x 100'	106,7 cm x 30,5 m	1 Roll	220062-00
50" x 100'	127,0 cm x 30,5 m	1 Roll	220063-00
60" x 100'	152,4 cm x 30,5 m	1 Roll	220064-00





Water-Resistant Poly Poster Matte / 8 mil

Properties	Specifications
Material	Polypropylene
Gauge	8 mil, 130g
CIE Whiteness	86
Brightness	90
Software Settings	The coating is engineered for more than 300% ink coverage. A photo matte, bond or uncoated paper setting is recommended as a starting point. However, a custom ICC profile is ideal for optimal results.
Light Fastness	Inkjet ink fading time is based on the inks you use and the print display environment. Dye-based inks fade noticeably under direct sunlight and interior applications where direct sunlight may fall on the image, and/or where fluorescent or other UV lighting is present. Though fading is inherent in all inkjet inks, certain UV-resistant inks, pigment-based inks, and UV-inhibiting coatings will extend image longevity. For light-fastness data and to determine an ink's suitability for the application, contact the ink manufacturer.
Finishing/Post Processing	It is recommended that you protect the printed side by mounting under glass, laminating, clear coating, or using photographic sleeves. This will help ensure image durability and stability. Pressure sensitive laminates provide the best bond. Applying the laminate by hand is not recommended.
Optimal Service Environment	59-86° F , 20-70% R.H.
Ideal Storage Conditions	68° F (20° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
Shelf Life	1 year from the BMG ship date when stored in proper conditions.



KODAK Water-Resistant Poly Poster Matte / 8 mil

Product Performance & Suitability: All of the descriptive information and recommendations for the use of Kodak products should be used only as a guide. Furnishing such information and commendations shall in no event constitute a warranty of any kind by BMG. All Purchasers of Kodak products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor the manufacturer shall be liable either in the tort in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect in agreement signed by officers of seller and manufacturer.

Eastman Kodak Company 343 State Street Rochester, NY 14650 USA +1-866-563-2533 in North America. Produced using Kodak Technology.
©Kodak, 2017. Kodak, Flexcel, Squarespot, Staccato and the Kodak Logo are trademarks of Kodak.
Subject to technical change without notice. U.FLX.865.0916.en.13

KODAKWFMedia.com

