



**KODAK**

Universal Satin Poly Poster / 8 mil

## Accurate reproduction, excellent results

### Designed to take advantage of the latest printer and ink technology

Expanded color gamut and higher Dmax KODAK PROFESSIONAL Inkjet Photo Paper, Glossy Finish has been updated to take advantage of the wider color gamut and improved ink technology of the latest generation of wide format inkjet printers from Canon, Epson and HP.

### Accurate reproduction

This next-generation paper has a higher Dmax to ensure that color captured in-camera reproduces more accurately, while producing deeper, richer black, an expanded dynamic range and additional detail in shadow areas.

### Trouble-free print production

Engineered to lay flat with little to no curl KODAK PROFESSIONAL Inkjet Photo Paper, Glossy Finish provides trouble-free print production with little to no curl.

### APPLICATIONS:

- Durable indoor banners
- Indoor posters
- Point of purchase displays

### FEATURES:

- Flexible, durable, tear-resistant base film
- Available in glossy and satin surfaces for a variety of viewing conditions
- Optimized for dye ink and thermal inkjet printers (expect slower dry times with pigmented inks)

US Size	Euro Size	Quantity	SKU
36" x 100'	91,4 cm x 30,5 m	1 Roll	084-00208A
42" x 100'	106,7 cm x 30,5 m	1 Roll	084-00209A
50" x 100'	127,0 cm x 30,5 m	1 Roll	084-00210A
60" x 100'	152,4 cm x 30,5 m	1 Roll	084-00211A





## Universal Satin Poly Poster / 8 mil

Properties	Specifications
<b>Material</b>	Polypropylene
<b>Gauge</b>	7.7 mil, 155g
<b>Whiteness</b>	>90
<b>Tear Strength</b>	NA
<b>Printer/Ink Compatibility</b>	Compatible with all thermal and piezo inkjet printers using water-based dye and pigment-based inks.
<b>Software Settings</b>	The photo gloss paper setting in most RIPs is appropriate; however, we recommend a custom ICC. The coating is engineered for more than 300% ink coverage. A photo gloss, satin or semi-gloss setting is recommended as a starting point. However, a custom ICC profile is ideal for optimal results.
<b>Light Fastness</b>	Inkjet ink fading time is based on the inks you use and the print display environment. Dye-based inks fade noticeably under direct sunlight and interior applications where direct sunlight may fall on the image, and/or where fluorescent or other UV lighting is present. Though fading is inherent in all inkjet inks, certain UV-resistant inks, pigment-based inks, and UV-inhibiting coatings will extend image longevity. For light-fastness data and to determine an ink's suitability for the application, contact the ink manufacturer.
<b>Finishing/Post Processing</b>	It is recommended that you protect the printed side by mounting under glass, laminating, clear coating, or using photographic sleeves. This will help ensure image durability and stability. Pressure sensitive laminates provide the best bond. Applying the laminate by hand is not recommended.
<b>Optimal Service Environment</b>	59-86° F , 20-70% R.H.
<b>Handling Recommendations</b>	Due to the absorptive nature of the coating, you should avoid touching the coated surface. It's always recommended that cotton gloves be used when handling inkjet coated materials.
<b>Ideal Storage Conditions</b>	68° F (20° C), 50% R.H. (a controlled environment is recommended); store in original packaging.
<b>Shelf Life</b>	1 year from the BMG ship date when stored in proper conditions.



## KODAK Universal Satin Poly Poster / 8 mil

**Product Performance & Suitability:** All of the descriptive information and recommendations for the use of Kodak products should be used only as a guide. Furnishing such information and recommendations shall in no event constitute a warranty of any kind by BMG. All Purchasers of Kodak products shall independently determine the suitability of the material for the purpose for which it is purchased. Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Neither the seller nor the manufacturer shall be liable either in the tort in contract for any loss or damage, direct, incidental or consequential (including loss of profits or revenue) arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect in agreement signed by officers of seller and manufacturer.

Eastman Kodak Company 343 State Street Rochester, NY 14650 USA +1-866-563-2533 in North America. Produced using Kodak Technology.  
©Kodak, 2017. Kodak, Flexcel, Squarespot, Staccato and the Kodak Logo are trademarks of Kodak.  
Subject to technical change without notice. U.FLX.865.0916.en.13

[KODAKWFMedia.com](http://KODAKWFMedia.com)

