




HP Universal Satin Photo Paper



The HP DesignJet printing system—the complete solution

HP DesignJet printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



See high-quality results at an economical price

See high-quality results

Produce vivid colors ideal for presentation graphics and indoor displays from posters and presentations to photo enlargements and art reproductions. HP Universal Satin Photo Paper provides high-quality results.

Enjoy high-quality results at an economical price

Look to HP printing materials to provide a high-quality choice at an economical price. HP Universal Satin Photo Paper is designed together with Original HP dye--based inks to provide the results you expect from your HP Designjet printer.

See reliable results, consistent performance

Experience the reliable performance of the HP large format printing system. HP Universal Satin Photo Paper is engineered with Original HP inks and the printer to deliver consistent image quality.

¹ With Original HP 83 UV inks. Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see HPLFMedia.com/hp/t/printpermanence.

² With Original HP 72 inks. Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminant— calculation assumes 6,000 Lux/12 hr day. For more information, see HPLFMedia.com/hp/t/printpermanence.

| Target customers | Applications | Benefits |
|-------------------------|--------------------------------------|--|
| Print service providers | Trade show and event displays | Rich, satin finish |
| Sign makers | Posters and presentations | Fingerprint resistant |
| Graphic artists | POP and retail displays | Up to 15 years indoor display permanence ¹ |
| Photo labs | Photo enlargements | Up to 2 months in-window display permanence unlaminated, up to 3 months laminated ² |
| | Art reproductions | Compatible with both Original HP dye-based inks |
| | Geographic Information Systems (GIS) | FSC®-certified paper ⁵ |

Technical specifications



HP Universal Satin Photo Paper

For the latest ICC profiles/paper presets, please visit HPLFMedia.com/hp/paperpresets.

| Weight | 171 g/m ² per ISO 536 Test Method | | | | | | | | | | | | | | | | |
|---|---|-----------------|------------|-----------|--------|--------|----------------------------------|--------------|-----------|--------|----------------------------------|--------------|-----------|--------|-----------------------------------|--------------|-----------|
| Thickness | 175 microns/6.9 mil per ISO 534 Test Method | | | | | | | | | | | | | | | | |
| Opacity | >90% per TAPPI T-425 Test Method | | | | | | | | | | | | | | | | |
| Brightness | >95% per TAPPI T-452 Test Method | | | | | | | | | | | | | | | | |
| Whiteness | 120 per CIE Ganz 82 Test Method | | | | | | | | | | | | | | | | |
| Finish | Satin | | | | | | | | | | | | | | | | |
| Operating temperature | 15 to 30° C / 59 to 86° F | | | | | | | | | | | | | | | | |
| Operating humidity | 30 to 70% RH | | | | | | | | | | | | | | | | |
| Display permanence (Indoor home or office) | Up to 15 years with Original HP 72 inks; up to 3 years with HP 727 inks ³ | | | | | | | | | | | | | | | | |
| Display permanence (Commercial in-window, unlaminated) | Up to 2 months with Original HP 72 inks; up to 1 month with HP 727 inks ⁴ | | | | | | | | | | | | | | | | |
| Display permanence (Commercial in-window, laminated) | Up to 3 months with Original HP 72 inks; up to 1 month with HP 727 inks ⁴ | | | | | | | | | | | | | | | | |
| Dry time | Less than 10 minutes (at 23° C, 50% RH) | | | | | | | | | | | | | | | | |
| Lamination | Yes, cold | | | | | | | | | | | | | | | | |
| Shelf life | 2 years, unopened in original package | | | | | | | | | | | | | | | | |
| Storage temperature | 5 to 40° C / 41 to 104° F | | | | | | | | | | | | | | | | |
| Storage humidity | 10 to 80% RH | | | | | | | | | | | | | | | | |
| Country of origin | Product of Germany | | | | | | | | | | | | | | | | |
| Ordering information | <table border="1"> <thead> <tr> <th>Product numbers</th> <th>Roll sizes</th> <th>UPC Codes</th> <th>Region</th> </tr> </thead> <tbody> <tr> <td>Q1420B</td> <td>610 mm x 30,5 m (24 in x 100 ft)</td> <td>848412013948</td> <td>Worldwide</td> </tr> <tr> <td>Q1421B</td> <td>914 mm x 30,5 m (36 in x 100 ft)</td> <td>848412013955</td> <td>Worldwide</td> </tr> <tr> <td>Q1422B</td> <td>1067 mm x 30,5 m (42 in x 100 ft)</td> <td>848412013962</td> <td>Worldwide</td> </tr> </tbody> </table> | Product numbers | Roll sizes | UPC Codes | Region | Q1420B | 610 mm x 30,5 m (24 in x 100 ft) | 848412013948 | Worldwide | Q1421B | 914 mm x 30,5 m (36 in x 100 ft) | 848412013955 | Worldwide | Q1422B | 1067 mm x 30,5 m (42 in x 100 ft) | 848412013962 | Worldwide |
| Product numbers | Roll sizes | UPC Codes | Region | | | | | | | | | | | | | | |
| Q1420B | 610 mm x 30,5 m (24 in x 100 ft) | 848412013948 | Worldwide | | | | | | | | | | | | | | |
| Q1421B | 914 mm x 30,5 m (36 in x 100 ft) | 848412013955 | Worldwide | | | | | | | | | | | | | | |
| Q1422B | 1067 mm x 30,5 m (42 in x 100 ft) | 848412013962 | Worldwide | | | | | | | | | | | | | | |
| Warranty | HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see HPLFMedia.com/mediawarranties . To obtain warranty service, please contact Brand Management Group customer support at HPLFMedia.com/hp/en/contactus . | | | | | | | | | | | | | | | | |

COLORPRO
TECHNOLOGY



The mark of
responsible forestry

³ Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see HPLFMedia.com/hp/printpermanence.

⁴ Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminant—calculation assumes 6,000 Lux/12 hr day. For more information, see HPLFMedia.com/hp/printpermanence.

⁵ BMG trademark license code FSC®-C115319, see fsc.org. HP trademark license code FSC®-C017543, see fsc.org. Not all FSC®-certified products are available in all regions. For information about HP large format printing materials, please visit HPLFMedia.com.

For detailed information on the HP large format printing materials portfolio and to order, see HPLFMedia.com

© 2022 HP Development Company, L.P. © 2022 Brand Management Group. The information contained herein is subject to change without notice.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of HP Development Company, L.P. and is used by Brand Management Group on license from HP Development Company, L.P.

